

Case No.: 7780/16
Serial No.: 10/005,391
Page 2

SPECIFICATION AMENDMENTS

Please amend the paragraph beginning on page 3, line 17 as follows:

al
"The tower 14 includes a plurality of telescoping, extendable segments 20, 21, 23, 25, 27 and a base segment 29 which, when nested, are movable to a stored position generally horizontal and parallel with the platform 18, as shown in FIG. 1. An arm 22, which may be powered by a hydraulic or electric motor 31, is provided to pivot the tower 14 from the stored position to an operating position generally vertical and perpendicular to the platform 18. To best support the erect tower, the pivot point is advantageously selected to be close to or directly over the rear double wheels 24 of the base 12."

Please amend the paragraph beginning on page 4, line 13 as follows:

62
After the self-propelled base 12 is driven to the desired test location, a power takeoff provides most necessary power. A six kilovolt diesel generator carried with the base is started to provide power to the electronics, as well as back up power for other functions. The base 12 is leveled with the outriggers, and cellular telephone network testing equipment such as a pod 40 containing an antenna and a continuous wave transmitter with an unmodulated signal is attached to the distal end 40 of the tower 14. The motor 31 then pivots the tower to the vertical position, so that the generally triangular in cross-section segments of the tower can be extended.